

Alsifix N

Hammer-in plug for the direct fixing of base rails in alsecco facade systems



AREAS OF APPLICATION

Constructional hammer-in plug with collar head and steel nail for the fixing of components in push-through installation, e.g. base rails.

PRODUCT PROPERTIES

- non-ageing

TECHNICAL DATA

Design

Diameter [mm]	required Anchoring depth [mm]/ usage categories	Length of shank [mm]
Anchor: 6/8	≥ 35	6/55, 8/75, 8/95

Accessories

Plastic grommet for tolerance compensation.

APPLICATION INSTRUCTIONS

Preparation

Adapt plug type and anchoring depth to the substrate.
Remove inappropriate mortar and ridges before fixing the rails.

Application

Make the drill hole depth at least 10 mm deeper than the length of the plug.
Position the drill holes at a right angle to the surface. The plug is installed by driving in the steel nail using a hammer.
Even out level differences in the substrate by using washers.
The mounting distance between the hammer-in plugs is approx. 30 cm for the structural fixing of components, e.g. base rails.
The ends of the rails must be fixed respectively in the last fixing point with a fastener.

PACKAGING INFORMATION

Colour	White
Packaging unit	Box 100 pieces

OTHER INFORMATION

Transportation	Not a hazardous material
----------------	--------------------------

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ