

Gerüststopfen Plus

Plugs made from impregnated flexible PU foam and render-effect cap for the rapid and secure sealing of scaffold anchor holes.



AREAS OF APPLICATION

Driving rain resistant and permanent sealing of putlog holes and backfilling for the finishing coat in alsecco facade systems. Suitable for hole diameters up to 17 mm.

PRODUCT PROPERTIES

- Plastic cap for scaffold anchor holes with a render-like texture
- Easy and quick application
- Joint width slowly expands
- Resistant to water penetration under driving rain.
- Good UV, weather and ageing resistance
- Water-vapour permeable
- Windproof

TECHNICAL DATA

| | |
|--------------------------|---|
| Material | Fine pored, non-shrink polyurethane soft foam Polyethylene core Softener free, modified polyacrylate impregnation |
| Building materials class | B1 according to DIN 4102-1 E according to DIN EN 13501-1 |
| Dimensions | Flexible PU foam: 28 mm diam Plastic cap with render-like texture: 30 mm diam Length incl. cap: 48 mm |
| Accessories | Milling tool for scaffold anchor plug Plus (length of milling tool: 145 mm with replaceable V2A stainless steel cutters) |

APPLICATION INSTRUCTIONS

Application

Insert the milling tool in the scaffold anchor hole, press in firmly and turn until the hole has been evenly deepened by 3 - 4 mm. Remove particles and dust from the hole. (If necessary, use a suitable insulation material - of the same kind applied throughout - to fill cavities behind the Anchor Plug Plus.)

Apply a light layer of a suitable insulation material, such as Joint Filler MS, around the milled area to provide an additional seal and fixing for the cap. Roll and press the impregnated flexible PU foam on the Anchor Plug Plus by hand to compress it. Insert the Anchor Plug Plus in the scaffold anchor hole until the plastic cap is flush with the surface of the render. Scrape off or remove any sealant emerging at the edges to create a clean edge. After the flexible PU foam has expanded and the Anchor Plug Plus sealant has hardened sufficiently, apply a suitable coat of facade paint.

STORAGE

Dry, protected against moisture and sunlight.

PACKAGING INFORMATION

Colour

Flexible PU foam: gray
Cap: white

Packaging unit

Please also refer to the current product range

OTHER INFORMATION

Information on safety

The information provided in the current safety data sheet applies.

Transportation

Not a hazardous material

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ