

Haftgrund Sc

Pigmented, filled primer for silicon-resin decorative renders



AREAS OF APPLICATION

Primer to even out colour variations and improve adhesion before applying final coat with silicon resin renders. For indoor and outdoor use.

PRODUCT PROPERTIES

- Water-vapour permeable
- Promotes adhesion
- Improves adhesion
- Absorbency regulating
- Reduces the risk of colour shading for a subsequent coating with pigmented silicone-resin renders
- Non-slip surface because quartz filled
- Provokes ideal and economical application of the decorative render

TECHNICAL DATA

Binder base	Acrylic resin dispersion
Specific gravity	approx. 1,7 g/cm ³
VOC value	EU limit value for the VOC content of this product (cat. A/h): 30 g/l (2010). This product contains < 10 g/l VOC.

APPLICATION INSTRUCTIONS

Substrate pre-treatment	All substrates must be stable, level, clean, dry and free of any residue, which can reduce adhesiveness. Prime substrates to be reinforced with Hydro penetrating primer.
Mixing	Ready to use Can be diluted with a max. of 20 % water.
Application	Can be applied using a brush, roller or spraying. Use short pile rolls for even application. It is recommended to use a primer in the colour of the subsequent textured

	render for unsealed textures.
Consumption	approx. 0,3 - 0,4 kg/m ² (approx. 200 - 250 ml/m ²) Determine the precise material requirements by means of a trial coating on the object.
Information about the weather	Temperatures cannot fall below +5 °C during application and drying.
Drying time	approx. 2 - 6 hours Dependent on temperature and relative humidity.
Cleaning of tools	In a fresh state with water.
Application by machine	Please request special information regarding machine processing.

STORAGE

Shelf life in original sealed packaging of at least 1 year when kept cool and protected against frost.

PACKAGING INFORMATION

Colour	Natural white and pigmented
Packaging unit	PP bucket approx. 20 kg net

OTHER INFORMATION

Information on safety	The information provided in the current safety data sheet applies.
Transportation	Not a hazardous material
Giscode	M-SF01 silicone resin paints, water soluble, active substances

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.

