

Kellerdeckendämmplatte Miwo 035 DP3

Mineral-wool insulation board for interior applications

AREAS OF APPLICATION

Non-combustible ceiling insulation board for systems with adhesive fixing, and with adhesive and mechanical fixing, for insulating interior ceilings.

PRODUCT PROPERTIES

- Area of application in accordance with DIN 4108-10: DI
- Approved according to the Ordinance on Hazardous Substances (GefStoffV), List of Prohibited Hazardous Substances (ChemVerbotsV and EU Directive 97/69 (note Q))
- Quality controlled according to DIN EN 13162
- Fireproof
- Good sound and thermal insulation
- Insulation board in accordance with DIN EN 13162 - T4-MU1-AFr25
- Edges: Straight

TECHNICAL DATA

Fire behavior	A1 according to DIN EN 13501-1
Thermal conductivity λ	Calculation value 0,035 W/(mK) in accordance with DIN 4108-4 Rated value λ_D : 0,034 W/(mK)
Dimensions	1.188 mm x 588 mm
Thickness	50 - 140 mm
Melting point	≥ 1000 °C
Accessories	Ceiling insulation screw DDS-Z Ceiling insulation disc DDT
Water vapour diffusion resistance μ	approx. 1 - 2 according to DIN EN 12086
Density	approx. 50 kg/m ³
Coatings	Exposed face with fleece lamination in natural white, slightly wavy, low visual quality of finish

APPLICATION INSTRUCTIONS

Substrate pre-treatment	Pretreat substrates according to the application instructions for the adhesive.
Application	<p>Apply adhesive using the spot-and-bead method. At least a 40 % bond must be achieved. If the substrate is very smooth, the adhesive may be applied using the ridged-bed method.</p> <p>Only fast-setting types of adhesive, such as Armatop MP or Dämmkleber MK (Thermastick MK) are suitable for fixing insulation boards to the ceiling.</p> <p>Additional mechanical fixings are required as stipulated in the standard administrative regulation of the technical building specifications (section D 2.2.2.22) for a weight $\geq 15 \text{ kg/m}^2$ using DDS-Z (ceiling insulation screw) and DDT (ceiling insulation disc) fixings.</p> <p>The insulation boards are butted close together.</p> <p>The vertical and horizontal joints of the boards must be kept free of adhesive.</p> <p>The front edges of the insulation boards are not laminated and may therefore be visible, depending on the layout grid. This must be taken into account when planning the layout grid.</p>

STORAGE

Dry, protected against moisture.

PACKAGING INFORMATION

Colour	Bonded face: Brown-yellow Exposed face: Natural white
Packaging unit	Please also refer to the current product range

OTHER INFORMATION

Transportation	Not a hazardous material
Waste code	17 06 04(class II waste disposal, household and construction waste disposal)

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.

