

Spachtelvlies

Matting to embed fillers



AREAS OF APPLICATION

Reinforcement matting for embedding in spray render LA and spray render FA on interior walls and ceilings.
To achieve smooth, even surfaces or to bridge hairline and shrinkage cracks.

PRODUCT PROPERTIES

- Waterproof
- Rotproof and resistant to chemicals

TECHNICAL DATA

Mortar category	Fibreglass matting
Density	approx. 45 g/m ²
Tensile strength	lengthwise: approx. 160 N / 5 cm crosswise: approx. 120 N / 5 cm

APPLICATION INSTRUCTIONS

Application	<p>Apply spray filler LA or spray filler FA mechanically or by hand. Then, comb through evenly using a notched trowel 4 x 6 x 4 mm (see alsecco tool program). Fold matting and place it into the wet spray filler bubble-free with an overlap of approx. 5 cm and fully insert it using a smoothing trowel. Make a double cut in the area of the overlap, remove the top and bottom section. Neatly smooth the seams.</p>
Consumption	approx. 1,05 m ² /m ²

PACKAGING INFORMATION

Colour	Natural white
Packaging unit	Roll 50 m ² , pallet 1200 m ²

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.

