

Traufelputz innen

Resin decorative render with scraped finish for interior use



AREAS OF APPLICATION

Decorative render for interior walls and ceilings.

PRODUCT PROPERTIES

- Crack resistant
- Water-vapour permeable
- Different design options due to various grain sizes
- Solvent and softener free (LEF)

TECHNICAL DATA

Binder base	Acrylic resin dispersion
Specific gravity	approx. 2,0 g/cm ³

APPLICATION INSTRUCTIONS

Substrate pre-treatment	<p>All substrates must be stable, level, clean, dry and free of any residue, which can reduce adhesiveness.</p> <p>We recommend a priming coat with Primer P, to improve workability before applying the decorative render.</p> <p>Absorbent substrates to be reinforced must be primed with Hydro penetrating primer. Depending on the absorbance of the substrate, can be deluted to max. 1:2 with water.</p>
Mixing	<p>Ready to use.</p> <p>Can be adjusted to a workable consistency with a max. of 2 % water.</p>
Application	<p>Apply in grain size with a rustproof steel trowel and after a brief period, spread with a plastic trowel using circular motions.</p> <p>Complete contiguous surfaces without stopping.</p>

Consumption	Grain size 1,5 mm approx. 2,5 kg/m ² Grain size 2,0 mm approx. 3,2 kg/m ² Determine the precise material requirements by means of a trial coating on the object.
Information about the weather	Temperatures cannot fall below +5 °C during application and drying.
Drying time	approx. 4 - 48 hours Dependent on temperature, layer thickness and relative humidity
Cleaning of tools	In a fresh state with water.
Application by machine	Please request special information regarding machine processing.

STORAGE

Shelf life in original sealed packaging of at least 1 year when kept cool and protected against frost.

PACKAGING INFORMATION

Colour	White and pigmented. Use material from one batch number for pigmented materials or contiguous surfaces.
Packaging unit	PP bucket approx. 25 kg net

OTHER INFORMATION

Information on safety	The information provided in the current safety data sheet applies.
Transportation	Not a hazardous material
Giscode	M-DF01 latex paints, solvent-free

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.

