

Wand- und Glättespachtel

Dispersible resin filler for interior use



AREAS OF APPLICATION

Scraper to scrape off uneven mineral and resin-bonded substrates.

PRODUCT PROPERTIES

- High filling capacity
- Can be easily sanded
- Low suction capacity
- Mineral percentage > 97%

TECHNICAL DATA

Binder base	Acrylic resin dispersion
Apparent density of set mortar	approx. 1,8 kg/dm ³
Fire behavior	A2-s1, d0 according to DIN EN 13501

APPLICATION INSTRUCTIONS

Substrate pre-treatment	All substrates must be stable, dry on the surface, clean and free of any residue, which can reduce adhesiveness.
Mixing	Ready to use
Application	Apply in the required layer thickness (max. 3mm) and swipe smooth levelly with a rustproof smoothing trowel. Rewash the inner corners using a radiator brush for smooth surfaces. Sand down the trowel marks.
Consumption	approx. 1,8 kg/m ² per mm layer thickness Determine the precise material requirements by means of a trial coating on the object.
Information about the weather	Temperatures cannot fall below +5 °C during application and drying.
Drying time	approx. 12 - 24 hours

Dependent on temperature, layer thickness and relative humidity

Cleaning of tools

In a fresh state with water.

Application by machine

Please request special information regarding machine processing.

STORAGE

Shelf life in original sealed packaging of at least 6 months when kept cool and protected against frost.

PACKAGING INFORMATION

Colour

White

Packaging unit

PP bucket approx. 25 kg net

OTHER INFORMATION

Information on safety

The information provided in the current safety data sheet applies.

Transportation

Not a hazardous material

Giscode

M-DF01 latex paints, solvent-free

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ