# **Eckschiene KU**

Edge guard for alsecco render and facade systems



## AREAS OF APPLICATION

Quick and reliable forming of neat corners and edges. Spot ground for vertical corner formation.

#### Areas of application:

Layer thickness approx.	Render or filler Spachtel	Note
3 mm	Armatop MP, Armatop Carbon, Armatop AKS, Armatop Quattro, Armatop Nova, Two in One light, Two in One, Spar Dash org	embedding completely (100%) into the reinforcing compounds
4-7 mm	Armatop L-Aero, Armatop Uni, Armatop A, Armatop por, Armatop Nova, Alsitop	embedding completely (100%) into the reinforcing compounds

Use rustproof rails or rails with a special polyester coating in regions with high humidity and areas close to the sea.

# TECHNICAL DATA

Material	Rod length
Synthetic with mesh	2,5 m



Product Data Sheet Eckschiene KU Page 2 of 2 PD 0374/0418/001

### **APPLICATION INSTRUCTIONS**

Reinforcement using system render or reinforcing compound.


Align flush and vertically.

Install the rails with PVC edge protection in a manner, which enables covering the rail joint by shifting the PVC profile.

Ensure a complete embedding in reinforcing compound or render.

Do not apply render to rails with PVC edges.

### **SKETCHES**



Corner rail KU - Dimensions in mm

### **PACKAGING INFORMATION**

### Packaging unit

Item	Container
Corner rail KU 08/12	Box 125 m
Corner rail KU 10/15	Box 125 m
Corner rail KU 10/23	Box 125 m
Corner rail KU 15/18	Box 125 m

#### alsecco GmbH

Kupferstraße 50 D-36208 Wildeck Phone 03 69 22 / 88-0 Fax 03 69 22 / 88-330 Internet: www.alsecco.de

