

# Kellerdeckendämmplatte Miwo 035

Mineral-wool insulation board for interior applications



## AREAS OF APPLICATION

Non-combustible ceiling insulation board for systems with adhesive fixing, and with adhesive and mechanical fixing, for insulating interior ceilings.

## PRODUCT PROPERTIES

- Area of application in accordance with DIN 4108-10: DI
- Approved according to the Ordinance on Hazardous Substances (GefStoffV), List of Prohibited Hazardous Substances (ChemVerbotsV and EU Directive 97/69 (note Q))
- Fireproof
- Insulation board in accordance with DIN EN 13162 - T4-TR1-AFr25
- Good sound and thermal insulation
- Quality controlled according to DIN EN 13162
- Edges: Straight

## TECHNICAL DATA

Fire behavior	A1 according to DIN EN 13501-1
Thermal conductivity $\lambda$	Calculation value 0,035 W/(mK) in accordance with DIN 4108-4 Rated value $\lambda_D$ : 0,034 W/(mK)
Dimensions	Size: 1200 x 400 mm
Thickness	60 - 140 mm
Melting point	$\geq 1000$ °C
Accessories	Ceiling insulation screw DDS-Z Ceiling insulation disc DDT
Water vapour diffusion resistance $\mu$	approx. 1 according to DIN EN 12086

Density	approx. 105 kg/m <sup>3</sup>
Coatings	Bonded face: White coated surface with uncoated bands Exposed face: White coated
Tensile strength at right angles to board (to DIN EN 13163)	≥ 1 kPa

## APPLICATION INSTRUCTIONS

Substrate pre-treatment	Pretreat substrates according to the application instructions for the adhesive.
Application	<p>Apply adhesive using the spot-and-bead method. At least a 40 % bond must be achieved. If the substrate is very smooth, the adhesive may be applied using the ridged-bed method.</p> <p>Only fast-setting types of adhesive, such as Armatop MP or Dämmkleber MK (Thermastick MK) are suitable for fixing insulation boards to the ceiling.</p> <p>Additional mechanical fixings are required as stipulated in the standard administrative regulation of the technical building specifications (section D 2.2.2.22) for a weight ≥ 15 kg/m<sup>2</sup> using DDS-Z (ceiling insulation screw) and DDT (ceiling insulation disc) fixings.</p> <p>The insulation boards are butted close together.</p> <p>The vertical and horizontal joints of the boards must be kept free of adhesive.</p> <p>The front edges of the insulation boards are not laminated and may therefore be visible, depending on the layout grid. This must be taken into account when planning the layout grid.</p> <p>If a superior finish is required, the surface can be coated with dispersion-silicate paint using an airless spray method.</p>

## STORAGE

Dry, protected against moisture.

## PACKAGING INFORMATION

Colour	White
Packaging unit	Please also refer to the current product range
Surface	White

## OTHER INFORMATION

Transportation	Not a hazardous material
Waste code	17 06 04(class II waste disposal, household and construction waste disposal)

**alsecco GmbH**  
Kupferstraße 50  
D-36208 Wildeck  
Phone 03 69 22 / 88-0  
Fax 03 69 22 / 88-330  
Internet: [www.alsecco.de](http://www.alsecco.de)

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ